

PLUMETT ULTIMAZ™

The UltimaZ™ is designed for pushing and blowing indoor and outdoor FTTH micro-cables. It is powered by most types of electrical drills and screwdrivers with an output torque exceeding 0.3 Nm at 250 – 500 RPM.



UltimaZ-P2P-V20



UltimaZ-P2P-Pusher



UltimaZ-P2P-F5 / F7

Standard equipment:

- 1 box for the UltimaZ and its accessories
- 1 set of tools
- 1 bottle of lubricant Micro jetting lube
- 1 operation and maintenance manual

Standard version	UltimaZ	UltimaZ	UltimaZ
Type	P2P-V20	P2P-F5 / P2P-F7	P2P-Pusher
Cable dia. [mm]	0.8-4.0	0.8-1.8 / 0.8-2.5	max. 4.0 (**)
Duct OD [mm]	3.0-12.0	3.0-12.0	max. 12.0 (**)
Pushing force [N]	0-20	5 / 7.5	-
Radial pressure on cable [N]	2-80	55 / 80	80
Recommended speed [m/min]	40	40	40
Max. air pressure [bar]	12	12	12
Dimension of apparatus l x w x h [mm]	223 x 136 x 140	168 x 136 x 150	168 x 136 x 150
Dimension of apparatus with case l x w x h [mm]	450 x 105 x 360	450 x 105 x 360	450 x 105 x 360
Weight of machine [kg]	2.050	1.500	1.400
Total weight [kg]	3.700	3.150	3.050

Specifications are subject to change without notice

(**) other sizes, please consult us

PLUMETT/ULTIMAZ™

Modular design according to the table below

	 Pusher	 Setting knob variable	 Setting knob ON/OFF	 Variable drive unit	 Fixed drive unit F5	 Fixed drive unit F7	 Set of air connection	 Counter VL 5	 Shaft protection
 UltimaZ-P2P-V20	X	X		X			X	X	X
 UltimaZ-P2P-F5	X		X		X		X	X	X
 UltimaZ-P2P-F7	X		X			X	X	X	X

MAIN ACCESSORIES



Lubricator L4,
for the continuous lubrication of cables
for a better Jetting performance



Micro Jetting Lube,
lubricant improving Jetting performance